


PLCC-4 Package Bi-Color SMD LED

VR 4KD8


Description

The constructive of this series of LEDs are different from the PCB type SMD LED. The lead-frame is of metal, reflector is made of thermoplastic and construct into this unique type of SMD LED. The Wavelengths and Luminous Intensities of this series are grouped under 20mA for uniformity.



Applications

- Dashboards and switch
- Backlight keypads
- Industrial control systems signal indicator
- Automotive features
- Telephone and fax backlighting or indicator



Electronic Optical Characteristics (@ 20mA):

Part Number	Emitted Color	λ (nm)		Iv (mcd)		VF (Volt)		View Angle (2 θ 1/2)	Lens
		λ_d	λ_p	Min	Typ.	Typ.	Max.		
VR 4KD8	Green 	573	575	18	28	2.0	2.4	130	Clear
	Yellow 	589	591	28	71	2.0	2.4		






Absolute Maximum Ratings (@ Ta=25°C)

Emitted Color	P _D (mW)	I _F (mA)	ESD(V)	I _R (uA) @VR=5V	Topr (°C)	Tstg (°C)
Green (573nm)	60	25	2000	10	-40~+85	-40~+90
Yellow (589nm)	60	25	2000	10	-40~+85	-40~+90

Note: Please take note the Absolute Maximum Rating values. Any operation beyond the specified ratings in this table will result degradation of LED life-span and may cause LED to fail.

Package Dimension:

unit:mm








Recommended Soldering Pad


Notes:

1. All dimensions are millimeters.
2. Tolerance is $\pm 0.2\text{mm}$ unless otherwise specified.
3. Specifications are subject to change without notice.

Optical Characteristics Curves




Reel Dimension:



Note:


Available in 8mm carrier tape on 178mm diameter reels. (2000 pieces)




Note:

A spacing of approximately 160mm between the front edge of tape


Tape Dimension:



Recommended re-flow soldering profile:



Recommended Pb-free re-flow soldering profile:



Note:

All the specifications listed in this data sheet are suitable for general electronic equipment, office equipment and communication devices. Kindly consult Sales Representatives for specific reliabilities request, Forward Voltage, Luminous Intensity, Wavelength, Radiant Power or Viewing Angle.