

Side View SMD LED 0.3mm Height

VS 7218


Description

The major breakthrough in VS 7218 is Blue color emitted package in 1.0 * 0.5 * 0.3mm dimension side look SMD LED. The dice used in this series is InGaN material. The advantages of InGaN are low power consumption and obtaining high luminous intensity under low current driving condition. The wavelengths and luminous Intensities of this series are grouped under 20 mA for uniformity. These LED are suitable for multiple usages in series connection applications.



Applications

- Backlighting applications
- Automotive features
- Status indication
- General lighting indicator



Electronic Optical Characteristics (at 20 mA):

Part Number	Emitted Color	λ (nm)		Lens Color	I_v (mcd)		View Angle	V_F (V)	
		λ_d	λ_p		Min.	Typ.		Typ.	Max.
VS 7218	Blue 	470	468	Clear	71	112	130	3.5	3.8

Absolute Maximum Ratings (at Ta=25°C)



P_D (mW)	I_{FP} (mA)	I_F (mA)	Iron Solder (°C)	I_R (uA)@ $V_R=5V$	T_{opr} (°C)	T_{stg} (°C)
90	100*	25	350 ± 5 for 3 sec.	50	-40~+85	-40~+100

Note: Please take note the Absolute Maximum Rating values. Any operation beyond the specify ratings in this table will result degradation of LED life-span and may cause LED to fail.

* I_{FP} : Peak Forward Current under 1/10 duty, 1KHz condition

Package Dimension:

unit:mm








Recommended Soldering Pad


Notes:

1. All dimensions are millimeters.
2. Tolerance is ± 0.2 mm unless otherwise specified.
3. Specifications are subject to change without notice.

Optical Characteristics Curves




Reel Dimension:



Note:


Available in 8mm carrier tape on 178mm diameter reels. (3000 pieces)




Note:

A spacing of approximately 160mm between the front edge of tape


Tape Dimension:



Recommended re-flow soldering profile:



Recommended Pb-free re-flow soldering profile:



Note:

All the specifications listed in this data sheet are suitable for general electronic equipment, office equipment and communication devices. Kindly consult Sales Representatives for specific reliabilities request, Forward Voltage, Luminous Intensity, Wavelength, Radiant Power or Viewing Angle.