


## Side View SMD LED 1.2mm Height

### VS 73C8

#### Description

The major breakthrough in VS 73C8 is True-green color emitted package in 2.7 \* 1.3 \* 1.2mm dimension side look SMD LED. This series of side emitting devices are operating under low current driving condition suitable for backlighting applications or applications call for light emitting from unique angle. Wavelengths and Luminous Intensities of this series are grouped under 20mA for uniformity. These LED are suitable for multiple usages in series connection



#### Applications

- Backlighting applications
- Automotive features
- Status indication
- General lighting indicator



#### Electronic Optical Characteristics (at 20mA):

| Part Number | Emitted Color                                                                                  | $\lambda$ (nm) |             | Lens Color | Iv(mcd) |      | View Angle | VF(V) |     |
|-------------|------------------------------------------------------------------------------------------------|----------------|-------------|------------|---------|------|------------|-------|-----|
|             |                                                                                                | $\lambda_d$    | $\lambda_p$ |            | Min.    | Typ. |            | Typ.  | Max |
| VS 73C8     | True-green  | 525            | 518         | Clear      | 112     | 180  | 120        | 3.5   | 3.8 |

#### Absolute Maximum Ratings (at Ta=25°C)


| P <sub>D</sub> (mW) | I <sub>FP</sub> (mA) | I <sub>F</sub> (mA) | Iron Solder(°C)    | I <sub>R</sub> (uA)@V <sub>R</sub> =5V | Topr(°C) | Tstg(°C) |
|---------------------|----------------------|---------------------|--------------------|----------------------------------------|----------|----------|
| 95                  | 100*                 | 25                  | 350 ± 5 for 3 sec. | 50                                     | -40~+85  | -40~+100 |

Note: Please take note the Absolute Maximum Rating values. Any operation beyond the specify ratings in this table will result degradation of LED life-span and may cause LED to fail.

\* I<sub>FP</sub>: Peak Forward Current under 1/10 duty, 1KHz condition

## Package Dimension:






unit:mm




## Notes:

1. All dimensions are millimeters.
2. Tolerance is  $\pm 0.2\text{mm}$  unless otherwise specified.
3. Specifications are subject to change without notice.

## Optical Characteristics Curves




## Reel Dimension:



Note:


Available in 8mm carrier tape on 178mm diameter reels. (2000 pieces)




Note:

A spacing of approximately 160mm between the front edge of tape


## Tape Dimension:



### Recommended re-flow soldering profile:



### Recommended Pb-free re-flow soldering profile:



### Note:

All the specifications listed in this data sheet are suitable for general electronic equipment, office equipment and communication devices. Kindly consult Sales Representatives for specific reliabilities request, Forward Voltage, Luminous Intensity, Wavelength, Radiant Power or Viewing Angle.