

Side View SMD LED 0.6mm Height

VS 75G8

Description

The major breakthrough in VS 75G8 is Green color emitted package in 2.1 * 1.0 * 0.6mm dimension side look SMD LED. The dice used in this series is AlGaInP rather than the conventional GaP and GaAsP/GaP. The advantages of AlGaInP are low power consumption and obtaining high luminous intensity under low current driving condition. The wavelengths and luminous Intensities of this series are grouped under 20mA for uniformity.



Applications

- Backlighting applications
- Automotive features
- Status indication
- Front panel indicator





Electronic Optical Characteristics (at 20mA):

Part Number	Emitted Color		λ (nm)		Lens	lv(mcd)		View	VF(V)	
			λd	λр	Color	Min.	Тур.	Angle	Тур.	Max
VS 75G8	Green		573	575	Clear	18	25	130	2.0	2.4

Absolute Maximum Ratings (at Ta=25 $^{\circ}$ C)

P _D (mW)	IFP(mA)	IF(mA)	Iron Solder (℃)	IR(uA)@V _{R=} 5V	Topr(℃)	Tstg(℃)
60	100*	25	350 ± 5 for 3 sec.	10	-40~+85	-40~+100

Note: Please take note the Absolute Maximum Rating values. Any operation beyond the specify ratings in this table will result degradation of LED life-span and may cause LED to fail.


*IFP: Peak Forward Current under 1/10 duty, 1KHz condition


Version:1.4 Spec: VS 75G8 Page 1 of 5




Package Dimension:

unit:mm







Recommended Soldering Pad


Notes:


- 1. All dimensions are millimeters.
- 2. Tolerance is ± 0.2mm unless otherwise specified.
- 3. Specifications are subject to change without notice.


Version:1.4 Spec: VS 75G8 Page 2 of 5





Optical Characteristics Curves












Version:1.4 Spec: VS 75G8 Page 3 of 5





Reel Dimension:



Note:

Available in 8mm carrier tape on 178mm diameter reels. (3000 pieces)






A spacing of approximately 160mm between the front edge of tape

Polarity

Tape Dimension:

unit: mm




Version:1.4

Spec: VS 75G8


Page 4 of 5



Recommended re-flow soldering profile:



Recommended Pb-free re-flow soldering profile:



Note:

All the specifications listed in this data sheet are suitable for general electronic equipment, office equipment and communication devices. Kindly consult Sales Representatives for specific reliabilities request, Forward Voltage, Luminous Intensity, Wavelength, Radiant Power or Viewing Angle.

Version:1.4 Spec: VS 75G8 Page 5 of 5