


0603 Package Bi-Color SMD LED

VS 2LD8


Description

This is Bi-Color SMD LED series with dimension 1.6 mm (L) * 0.8 mm (W) * 0.5 mm (H) The unique of these LEDs are made from AlGaInP and InGaN chips that provide high luminous intensity at low driving current. The lens design provides 120 degree viewing angle and suitable for backlighting purpose. The available colors are Red/Green, Yellow/Blue or even Red/Blue. Any color combinations specified by customers can be accepted.



Applications

- Industrial control systems signal indicator
- Automotive features
- Front panel indicator
- Status indication



Electronic Optical Characteristics (at 20mA):

Part Number	Emitted Color	λ (nm)		Iv(mcd)		VF(Volt)		View Angle	Lens
		λ_d	λ_p	Min	Typ.	Typ.	Max.		
VS 2LD8	Red 	624	632	45	90	2.0	2.4	120	Clear
	Blue 	470	468	28	45	3.3	3.7		

Absolute Maximum Ratings (at Ta=25°C)





Emitted Color	P _D (mW)	I _F (mA)	I _{FP} (mA)	I _R (μ A)@VR=5V	Topr(°C)	Tstg(°C)
Red	60	25	60*	10	-40~+85	-40~+90
Blue	110	25	60*	10	-40~+85	-40~+90

Note: Please take note the Absolute Maximum Rating values. Any operation beyond the specified ratings in this table will result degradation of LED life-span and may cause LED to fail.

* Peak forward current (duty 1/10 at 1KHz)

Package Dimension:

unit:mm








Recommended Soldering Pad


Notes:

1. All dimensions are millimeters.
2. Tolerance is $\pm 0.2\text{mm}$ unless otherwise specified.
3. Specifications are subject to change without notice.

Optical Characteristics Curves




Reel Dimension:



Note:


Available in 8mm carrier tape on 178mm diameter reels. (3000 pieces)




Note:

A spacing of approximately 160mm between the front edge of tape


Tape Dimension:



Recommended re-flow soldering profile:



Recommended Pb-free re-flow soldering profile:



Note:

All the specifications listed in this data sheet are suitable for general electronic equipment, office equipment and communication devices. Kindly consult Sales Representatives for specific reliabilities request, Forward Voltage, Luminous Intensity, Wavelength, Radiant Power or Viewing Angle.